

### 1.5 HP / 8 Gallon Constant Run

#### Wheeled Portable 15 Amp Twin Tanks

- 6.5 CFM delivered @ 100 PSI enables quick recovery
- Twin cylinder, cast iron, oil lubricated pump with Emglo
- Low profile design for easy maneuverability
- On/Off constant run design for reduced breaker tripping
- Pneumatic tire improves worksite mobility
- Ball valve drain for quick and thorough tank draining

D55170



### 2 HP / 4 Gallon Hand Carry Twin Tanks

- 4.5 CFM delivered @ 100 PSI, enables speedy recovery
- Oil lubricated pump improves durability
- Dual soft start valves assist in cold weather start up
- 4 gallon twin stack tank design with proven acceptance in the market
- Cast iron cylinder enhances pump life


D55153



### 2.75 HP / 4 Gallon Hand Carry Single Tank

- 4.5 CFM delivered @ 100 PSI, recovers in under 15 seconds
- New ergonomic design for easy portability
- Protected components for maximum durability
- Oil lubricated pump allows for increased life
- ASME coded 4 gallon OSHA recognized tank
- Dual soft start valves assist in cold weather start up
- Ball valve drain allows for quick and thorough tank draining

D55155



### 5.5 HP / 8 Gallon Gas Wheeled Portable Twin Tanks

- 8.9 CFM delivered @ 100 PSI for quick recovery
- Twin cylinder, cast iron, oil lubricated pump with Emglo
- Low profile design for easy maneuverability
- 5.5 HP Honda OHV GX gas engine provides proven reliability and durability
- Low oil shut off provides greater engine protection
- Automatic idle control for reduced fuel consumption

D55270



### 1.5 HP / 8 Gallon Wheeled Portable

- Splash lubricated cast iron crankcase
- Quality cast iron single stage compressor
- Industrial UL listed motor
- Large canister intake filter
- 10 inch fly wheel for extra cooling and longer life
- Pneumatic tire with tube and steel hub
- Belt tightening system pulls engine straight to ensure constant belt alignment
- Stainless-steel braided discharge hose
- 2 yr pump exchange program

AC1-PE15-08M



### 2 HP Electric Twin Stack

- Cast iron cylinder
- Regulator and two gauges for tank and outlet pressure
- 5 Gallon powder coated tank assembly
- Start/Stop control set at 95-125 PSI
- Thermal overload motor protection
- Stainless-steel braided discharge hose
- Drain valves and pressure relief valve
- Oil lubricated crankcase
- 120 volt single phase 60 Hz. motor with 15 amp plug

AC1-HE02-05M1



### 5.5 HP / 8 Gallon Gas Wheeled Portable Honda Gasoline Engine

- Splash lubricated cast iron crankcase
- Quality cast iron single stage compressor
- Pneumatic idle control for added safety
- Directional air shroud to reduce temperature of compressor
- Large canister intake filter
- 10 inch fly wheel for extra cooling and longer life
- 2 yr. pump exchange program
- Stainless-steel braided discharge hose

AC1-PH55-08M

## HITACHI



### 2 HP / 4 Gallon Air Compressor Twin Stack, Oil-lube

- 4.0 CFM at 90 PSI
- Direct Drive electric motor
- Line regulator with gauge
- O-ring on drain-cock makes valve easy to open and close
- Vertically stacked twin tanks, 2 gallon capacity each
- Includes: Synthetic Oil SAE 5W50 8oz. 19210 and Oil dipstick 881469

EC12