

FALL PROTECTION



850



8183



216WLS



Lanyards

- U201RLS-8 Positioning 6'
- U216WLS Shock absorbing 6'
- T5111 Titan Shock absorbing 6'
- UT7314 Titan 6'/Cross arm strap
- UT911R Titan Rope positioning 6'

Tie Off Adaptors

- U8183 Tie off adaptor

Harnesses

- U850 Pass Thru Harness
- U850-4 Full Body Universal Size
- UT4000 Titan Pass thru Harness
- UT4500 Titan Full Body Universal Size



3101001



3101051

Web Talons

Swivel Snap Hook

- 8 or 16 ft. self retracting lifeline is engineered for reliable protection
- Durable and lightweight construction only weighs 4.7 lbs
- Stops a fall within inches and limits fall arrest forces to under 900 lbs

- U3101001 8 ft. Web Talon w/swivel snap hook
- U3101051 16 ft. Web Talon w/swivel snap hook

Roof Anchor Kit

- Compliance-in-a-Can™ delivers a fundamental fall protection system with performance, safety and exceptional value
- 3-point adjustable harness with pass-thru leg straps and back D-ring
- 50 ft. lifeline and rope adjuster with 3 ft. shock absorbing lanyard
- Removable roof anchor that provides a 5,000 lb. anchorage point

UAA7051A Roof Anchor Kit

UAA7051AP Roof Anchor Kit (pallet of 16)

5/8" Rope Grab

- Lad-Saf® mobile type rope grab with hands-free operation automatically follows the worker
- Utilizes both inertia and cam locking systems for added safety, prevents "panic-grab"
- Energy absorbing design reduces forces generated during a fall for added safety

U5000335 5/8" Rope Grab

Cable

20' SRL Swivel Snap Hook

- Ultra-Lok SRLs are durable yet lightweight (9 lbs.) polyurethane construction
- Stainless components and 3/16" galv. cable provide corrosion resistance
- Stops falls within inches and limits fall arrest forces to 900 lbs. or less

U3504433 20ft. Galv. Cable SRL w/ Swivel Snap Hook

Cable SRL

30ft. 5mm Galvanized

- JRG SRLs provide an economical solution without compromising performance or safety
- Durable thermoplastic construction weighs under 10 lbs

UAD212AG 30 ft. 5mm Galv. Cable SRL (no impact indicator)



1224406

Shockwave 2 Lanyard

Twin-Leg 100% Tie-Off

- Stretchable design for complete freedom of movement
- Expands to 6 ft., retracts to 4-1/2 ft. reducing trip fall hazards, dragging and snagging
- Abrasion resistant nylon tubular webbing construction
- Easy-to-use self locking snap hooks at each end
- Limits fall arrest forces to 900 lbs. or less for added safety

U1224406 100% Shockwave Lanyard w/ Snap Hooks Each End

Lanyards

- Lightweight and polyester web construction
- Limits arresting forces to 900 lbs. or less for added safety

Shock Absorbing 6' E-Z Stop

U1220006 6 ft. E-Z Stop II Shock Absorbing Lanyard

Shock Absorbing 6' Wrap Box

U1221901 6 ft. Wrap Box Shock Absorbing Lanyard

6 ft. Shock Absorbing, Rebar Hooks Both Ends

UAE57620 100% Shock Absorbing Lanyard w/ Rebar Hooks Ea End

Concrete Anchor Strap

- 3-1/2 ft. disposable anchor strap for concrete forms - 5,000 lb. fall arrest anchorage point
- Loop on end slips over rebar, concrete is then poured on top of loop and wear pad
- Durable polyester web construction w/full length wear pad for abrasion resistance

U2100050

Tie-off Adaptor 3'

- Ease-of-use - 5,000 lb. strength
- Meets or exceeds OSHA and ANSI requirements

U1003000 3' Tie-off adaptor

Harness

Universal Delta Back & Side D-ring

- Delta No-Tangle™ design
- Belt and pad for added back support
- Shoulder pads for comfort
- Tongue buckle leg straps for accurate adjustability and a "custom" fit
- Color-coded straps

U1101655 Univ. Delta w/ Back & Side D-ring & Lg. Belt w/ Back Pad

Harnesses

Universal Delta

- Delta No-Tangle™ design provides ultimate comfort and ease-of-use
- Tongue buckle leg straps for accurate adjustability and a "custom" fit
- Lightweight design
- Color-coded straps
- Meets or exceeds OSHA and ANSI requirements

Univ. Delta Back D-ring

U1102000 w/ Back D-ring

Universal Delta Back & Side D-ring

U1102008

w/ Back & Side D-ring

Universal Pro Harness

- Back & Side D-ring
- Back Pad & Belt w/shoulder Pads
- Economical contractor harness provides exceptional performance, safety and comfort
- 5-point adjustment with tongue buckle leg straps
- Durable polyester webbing
- Meets or exceeds OSHA and ANSI requirements

UAB104A20 Univ. Pro w/ Back & Side D-ring



1101655



1102000

If You Don't See It, Call And Ask About Our Special Order Program



Harnesses

Medium Exofit

- Revolutionary harness design for maximum comfort and performance
- Superior "X" design padding wraps around the wearer for no-tangle donning
- Built-in shoulder, back, leg, hip and seat padding provides ultimate comfort
- 5-point adjustment system with one-handed quick-connect buckles for quick and easy adjustment - a perfect fit
- Moisture-wicking lining keeps you cool and dry all day
- Lycra edging prevents chafing
- Lightweight mesh in back for full ventilation
- Meets or exceeds OSHA and ANSI requirements

Back & Side D-rings

U1107976
Med. Exofit w/ Back D-ring

Back & Side D-ring & Body Belt with Back Pad

U1108501 Med. Exofit w/ Back & Side D-ring & Back Pad

Back & Side D-rings

U1108576 Med. Exofit w/ Back & Side D-ring



Lanyard, Decelerator

- Polyester decelerator energy absorbing lanyard
- 2 double locking snap hooks
- 6 ft.
- Meets or exceeds ANSI and OSHA standards

UFPD29811/6



Universal Harnesses

Back D-ring

- Economical harness provides exceptional performance and safety
- 5-point adjustment with pass-thru leg straps provides a perfect fit
- Durable polyester webbing stands up to the environment
- Meets or exceeds OSHA and ANSI requirements

Back D-ring


UAB17530 Univ. Compliance w/ Back D-ring

6' With Bag

UAB17533 Harness & Lanyard, 6 ft. w/ Bag

Back & Side D-ring

UAB17540 Univ. Compliance w/ Back & Side D-ring



Adjust-A-Net

- Meets or exceeds national and international safety requirements

- No liner

15' X 25'
3U0-ADJ-15X25

20' X 30'
U30-ADJ-20X30

25' X 50'
U30-ADJ-25X50

Sling, Web Cross-Arm Anchor 6'

- Flexible anchorage
- Cross arm anchor sling
- 2" heavy duty nylon web, with sewn loop and large D ring which passes through the loop to tighten around the anchor
- Meets and exceeds ANSI and OSHA standards

UFP04/6 6 ft.



FPD698/1DGP



FPD698/1DP



FP700/1D

Sized Harness

- Light weight with pass-through leg buckles, back D-ring
- Sized full body harness provides the ultimate in comfort and safety
- Applications: general purpose, warehouse picking, and construction
- Nylon webbing and forged hardware mean long-term wear and safety
- Sub-pelvic strap to help evenly distribute the forces generated in a fall
- Meets and exceeds ANSI and OSHA standards

UFP700/1DS

Harness/D-ring, sm, nylon

UFP700/1DM

Harness/D-ring, med, nylon

UFP700/1DL

Harness/D-ring, lg, nylon

UFP700/1DXL

Harness/D-ring, xl, nylon

UFP700/1DXXL

Harness/D-ring, xxl, nylon

Universal Harness

- Lightweight full body vest style universal fit harness
- Polyester webbing provides added UV protection and chemical resistance
- Sub-pelvic strap to help evenly distribute the forces generated in a fall
- Grommeted leg connectors with 1 back D ring

UFP759/1DGP

Universal Harnesses


- Polyester universal full body harness
- Polyester webbing resists chemicals

Grommeted legs


UFPD698/1DGP

Pass thru buckles

UFPD698/1DP



FP21122/6



FP28822/6

5/8" x 6' Rope Lanyard - 2 Snaps

- Nylon rope lanyard
- 2 self-locking snap hooks
- 6 ft. long
- Positioning & restraint assembly
- Meets and exceeds ANSI and OSHA standards

UFP21122/6

Lanyard Decelerator

- Warning flag indicates if lanyard has been in a fall
- Engineered to limit arresting forces to 900 lbs. or less
- Tough nylon tube jacket that functions as a back-up lanyard
- 2 self-locking snap hooks

UFP28822/6